


## GPS & 4G/LTE External Antennas





Product Number: ATGLTE9030-2.5BA

### 1. Specification

Sample Photo	
	
<b>A. Electrical Characteristics</b>	
Frequency	1575.42 MHz; 824-880MHz; 960-1710MHz; 1880-1990MHz; 2100-2700MHz
S.W.R.	GPS: $\leq 2.0$ @ 1575.42MHz; LTE: $< 3.5$ @ 824-960MHz; $< 5.5$ @ 1710-2700MHz
Antenna Gain	4 dBi @ 1575.42MHz, 30 dBi @ 1575.42 MHz LNA 0.5 dBi @ 824~960 MHz 2.5 dBi @ 1710~2700 MHz
Polarization	Omni-directional
Impedance	50 Ohm
<b>B. Material &amp; Mechanical Characteristics</b>	
Material of Radiator	PCB
Material of Plastic	ABS
Cable Type	RG 174
Connector Type	SMA Male
Connector Pull Test	$\geq 3.0$ Kg
Connector Torque Test	100~500 g.cm
<b>C. Environmental</b>	
Operation Temperature	- 40 °C ~ + 85 °C
Storage Temperature	- 40 °C ~ + 85 °C

# ATGLTE Series

## 2. Antenna - S Parameter Test Data



## 3. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification
M1	Vibration	MIL-STD-202G, 201A Amplitude: 0.03 inch (0.76mm); Freq: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol.<= 5%
M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol.<= 5%
M3	Solderability	MIL-STD-202G, 210F, cond. A Solder iron: 350±10°C; Duration: 5 seconds	1. Mounted on PCB 2. No Visual Damage
M4	Terminal-Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M5	Terminal-Torque Test	MIL-STD-202G, 211A, cond. E Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M6	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	MIL-STD-202G, 101E, cond. B Temp: 35°C; RH: >= 95%; NaCl solution: >= 5%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E2	Humidity	MIL-STD-202G, 103B, cond. B Temp: 40°C; RH: >= 95%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E3	Thermal Shock	1 Cycle: - 40°C (30 minutes) to + 85°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E4	Life (High Temp.)	MIL-STD-202G, 108A, cond. A Temp: 85°C; Time: 96 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2002/95/EC
R2	PFOS	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC
R3	PFOA	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC

# ATGLTE Series

## 4. Mechanical Drawing

