


M12 female Y type splitter overmold cable connector



M 1 2

Technical parameters

Shell material	Copper/Zinc	Insulation resistance	≥100mΩ
Core material	PA66	Contact resistance	≤10mΩ
Overmold material	PVC/TPU [®]	Degree of protection	IP67/IP68
Terminal material	Phosphor copper	Mating cycle	≥500次
Temperature	-40°C~+80°C	Cable diameter	

Electric parameter

pin number	code type				rated current	rated voltage		cable size		cable material	dealing at the end cable
	A	B	C	D		A/C	D/C	AWG	mm ²		
2					4A	250V	250V	22	0.34	PVC/PUR	
3					4A	250V	250V	22	0.34	PVC/PUR	
4					4A	250V	250V	22	0.34	PVC/PUR	
5					4A	60V	60V	22	0.34	PVC/PUR	- no dealing - customized
6					2A	30V	30V	24	0.25	PVC/PUR	- strip and tinn - to other connector
8					2A	30V	30V	24	0.25	PVC/PUR	
12					1.5A	30V	30V	26	0.14	PVC/PUR	
17					1.5A	30V	30V	26	0.14	PVC/PUR	

Order method

<p>Ⓐ Regular type</p> <p>M12-<input type="text"/>-Y-<input type="text"/>-S-<input type="text"/>-<input type="text"/>-<input type="text"/></p> <p>pin number code type (except A type) cable length cable material[®] others</p>	<p>Ⓑ Customized</p> <p>M12-<input type="text"/>-Y-<input type="text"/>-S-<input type="text"/>-<input type="text"/></p> <p>pin number code type (except A type) customized item number others</p>
--	---